



QUANTUM® Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 1/9/2019 Supersedes: 7/7/2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Metal Processing Fluid
Product code : T7340
Type of product : Metal working fluids
, Emulsifiable
Synonyms : Hydraulic oils
Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Industrial/Professional use spec : Use in functional fluids
Distribution
Formulation & (re)packing of substances and mixtures
Function or use category : Metal working fluids

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

QUANTUM LUBRICANTS

G. Karamichalis & Co EE

Dim. Gounari 35

165 62 Glyfada - Attiki

Tel: 0030 210 963 85 10

quantum@quantum-oils.com

1.4. Emergency telephone number

Emergency number : Unified emergency number: +30 210 7793777

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2 H319
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazardous ingredients :

Fatty acid monoethanolamid polyglycoether; 2-n-butyl-benzo[d]isothiazol-3-one

Hazard statements (CLP) :

H319 - Causes serious eye irritation.
H412 - Harmful to aquatic life with long lasting effects.

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P264 - Wash hands, forearms and face thoroughly after handling. P273 - Avoid release to the environment. P280 - Wear protective gloves, eye protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH208 - Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction. EUH210 - Safety data sheet available on request.

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : CLP Calculation method

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (REACH-no) 01-2119484627-25-0035; 01-2119484627-25-0025;01-2119471299-27-0019	0 – 100	Not classified
Distillates (petroleum), solvent-dewaxed heavy paraffinic	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (REACH-no) 01-2119471299-27-0016;01-2119471299-27-0003	0 – 100	Not classified
fatty alcohol, ethoxylated	(CAS-No.) 68920-66-1 (EC-No.) 500-236-9 (REACH-no) 01-2119489407-26	< 7	Skin Irrit. 2, H315 Aquatic Chronic 2, H411
Fatty acid monoethanolamid polyglycoether	(CAS-No.) 157707-44-3 (EC-No.) Polymer	< 1.6	Eye Dam. 1, H318
Isotridecan-1-ol	(CAS-No.) 27458-92-0 (EC-No.) 248-469-2 (REACH-no) 01-2119488528-21	< 0.6	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8 (REACH-no) 01-2119475104-44	< 0.6	Eye Irrit. 2, H319
2-n-butyl-benzo[d]isothiazol-3-one	(CAS-No.) 4299-07-4 (EC-No.) 420-590-7 (EC Index-No.) 606-079-00-3 (REACH-no) 01-0000016721-74	< 0.2	Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Comments : Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.
Not available REACH number or substance is not currently required for registration under REACH

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If medical advice is needed, have product container or label at hand. Never give anything by mouth to an unconscious person.

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. Get immediate medical advice/attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause headache, nausea and irritation of respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Direct contact with the eyes is likely to be irritating, redness, itching, tears.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting. Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area. Eliminate all ignition sources if safe to do so.
Firefighting instructions	: DO NOT fight fire when fire reaches explosives. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Clean up any spills as soon as possible, using an absorbent material to collect it. Eliminate every possible source of ignition. Do not handle until all safety precautions have been read and understood. Notify authorities if product enters sewers or public waters.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing mist, vapours.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area. Stop release. Cover spill with non combustible material, e.g.: sand/earth. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
-------------------------------	--

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Use only non-sparking tools.
Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible products : Oxidizing agent. Strong acids. Strong bases.
Incompatible materials : Sources of ignition.

7.3. Specific end use(s)

Product information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

QUANTUM Metal Processing Fluid

EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	5 mg/m ³
IOELV STEL (mg/m ³)	10 mg/m ³

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	5 mg/m ³
IOELV STEL (mg/m ³)	10 mg/m ³

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	5 mg/m ³
IOELV STEL (mg/m ³)	10 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Gloves. Protective clothing. Protective goggles.

Hand protection:

protective gloves: neoprene gloves, PVA. Chemical resistant PVC gloves (to European standard EN 374 or equivalent). EN 420

Eye protection:

Safety glasses. EN 166. EN 168

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. EN 405

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: 9.5 5% Water Solution
pH solution	: 9.5 @5%
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -15 °C
Boiling point	: > 315 °C
Flash point	: 160 °C
Auto-ignition temperature	: > 315 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: < 10 Pa
Relative vapour density at 20 °C	: > 1
Relative density	: No data available
Density	: 0.884 g/ml
Solubility	: Water miscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 45 mm ² /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401 method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (OECD 403 method)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401 method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402 method)

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LC50 inhalation rat (mg/l)	> 5 mg/l/4h (OECD 403 method)
Skin corrosion/irritation	: Not classified pH: 9.5 5% Water Solution
Serious eye damage/irritation	: Causes serious eye irritation. pH: 9.5 5% Water Solution
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)

QUANTUM Metal Processing Fluid

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

QUANTUM Metal Processing Fluid

Viscosity, kinematic	45 mm ² /s @40°C
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LC50 fish 1	> 100 mg/l (OECD 203 method)
EC50 Daphnia 1	> 10000 mg/l (OECD 202 method)
EC50 72h algae (1)	> 1000 mg/l (OECD 201 method)
NOEL, aquatic invertebrates, Chronic	< 1 mg/l (21 days, (OECD 211 method))
NOEL, algae, Chronic	> 100 mg/l (72 Hours, (OECD 201 method))
NOEL, microorganisms, Chronic	> 1.93 mg/l (10 minutes, DIN 38412)
NOEL, daphnia, Chronic	> 10 mg/l (21 days)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LC50 fish 1	> 100 mg/l (OECD 203 method)
EC50 Daphnia 1	> 10000 mg/l (OECD 202 method)
EC50 72h algae (1)	> 1000 mg/l (OECD 201 method)
NOEL, aquatic invertebrates, Chronic	< 1 mg/l (21 days, (OECD 211 method))
NOEL, algae, Chronic	> 100 mg/l (72 Hours, (OECD 201 method))
NOEL, microorganisms, Chronic	> 1.93 mg/l (10 minutes, DIN 38412)
NOEL, daphnia, Chronic	> 10 mg/l (21 days)

Isotridecan-1-ol (27458-92-0)

LC50 fish 1	0.31 mg/kg (OECD 203 method)
EC50 Daphnia 1	0.291 (OECD 202 method)

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-n-butyl-benzo[d]isothiazol-3-one (4299-07-4)

LC50 fish 1	0.15 mg/l
EC50 Daphnia 1	0.093 ppm

12.2. Persistence and degradability

QUANTUM Metal Processing Fluid

Persistence and degradability	Not readily biodegradable, according to appropriate OECD test due to properties of several components.
-------------------------------	--

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Persistence and degradability	Not readily biodegradable, according to appropriate OECD test due to properties of several components.
Biodegradation	< 32 % (OECD 301B method)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Persistence and degradability	Not readily biodegradable, according to appropriate OECD test due to properties of several components.
Biodegradation	< 32 % (OECD 301B method)

Isotridecan-1-ol (27458-92-0)

Persistence and degradability	Readily biodegradable.
Biodegradation	> 90 %

12.3. Bioaccumulative potential

QUANTUM Metal Processing Fluid

Bioaccumulative potential	Bioaccumulative potential.
---------------------------	----------------------------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Kow)	3.5 – 6 Moderately bioaccumulative
---	------------------------------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Partition coefficient n-octanol/water (Log Kow)	3.5 – 6 Moderately bioaccumulative
---	------------------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

QUANTUM Metal Processing Fluid

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

Component

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	PBT: not relevant – no registration required vPvB: not relevant – no registration required
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	PBT: not relevant – no registration required vPvB: not relevant – no registration required
Isotridecan-1-ol (27458-92-0)	PBT: not relevant – no registration required vPvB: not relevant – no registration required

12.6. Other adverse effects

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.
Product/Packaging disposal recommendations	: hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ecology - waste materials : Avoid release to the environment.
European List of Waste (LoW) code : 12 01 07* - mineral-based machining oils free of halogens (except emulsions and solutions)
12 01 09* - machining emulsions and solutions free of halogens

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

No supplementary information available

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
3.	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether; 2-n-butyl-benzo[d]isothiazol-3-one	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008
3(b)	QUANTUM Metal Processing Fluid ; fatty alcohol, ethoxylated ; Isotridecan-1-ol ; Fatty acid monoethanolamid polyglycoether ; 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether ; 2-n-butyl-benzo[d]isothiazol-3-one	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	QUANTUM Metal Processing Fluid ; fatty alcohol, ethoxylated ; Isotridecan-1-ol ; 2-n-butyl-benzo[d]isothiazol-3-one	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
55.	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	2-(2-butoxyethoxy)ethanol (DEGBE)

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

For the following substances of this mixture a chemical safety assessment has been carried out

Distillates (petroleum), hydrotreated heavy paraffinic
Distillates (petroleum), solvent-dewaxed heavy paraffinic

SECTION 16: Other information

Indication of changes:

Composition/information on ingredients.

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Other information : None.

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Eye Irrit. 2	H319
Aquatic Chronic 3	H412

QUANTUM Metal Processing Fluid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

QUANTUM SDS design

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.